Selvam College of Technology (Autonomous), "A" Grade by NAAC, UGC recognized 2(f) Status, Approved by AICTE – New Delhi, Affiliated to Anna University Namakkal – 03. www.selvamtech.edu.in

DEPARTMENT OF CIVIL ENGINEERING CE3502- STRUCTURAL ANALYSIS-1

UNIT-2- SLOPE DEFLECTION METHOD

2 MARKS QUESTIONS

| S.No | QUESTIONS | co's |
|------|--|------|
| 1. | What are the assumptions made in slope-deflection method? | CO2 |
| | i) Between each pair of the supports the beam section is constant. | |
| | ii) The joint in structure may rotate or deflect as a whole, but the angles | |
| | between the members meeting at that joint remain the same. | |
| | What is the limitation of slope-deflection equations applied in structural | CO2 |
| 2. | analysis? | |
| | 1) It is not easy to account for varying member sections. | |
| | 2)It becomes very cumbersome when the unknown displacements are large in | |
| | number. | |
| | Mention the causes for sway in portal frames. | CO2 |
| | Because of sway, there will be rotations in the vertical members of a frame. This | |
| 3. | causes moments in the vertical members. To account for this, besides the | |
| | equilibrium, one more equation namely shear equation connecting the joint- | |
| | moments is used. | |
| | Explain the use of slope deflection method. | CO2 |
| 4. | i) It can be used to analyze statically determinate and indeterminate beams and | |
| | frames. | |
| | ii) In this method it is assumed that all deformations are due to bending only. | |
| | iii) In other words deformations due to axial forces are neglected. | |
| | iv) The slope-deflection equations are not that lengthy in comparison. | |
| 5. | Write down the slope deflection equation for a beam AB fixed at A and B | CO2 |
| | subjected to a settlement δ at B. | |
| | $M_{AB} = M_{FAB} + \frac{2 EI}{L} \left(2\theta_A + \theta_B + \frac{3 \delta}{L} \right)$ | |
| | $M_{BR} = M_{FBR} + \frac{2EI}{L} \left(\theta_A + 2\theta_B + \frac{36}{L} \right)$ | |

Selvam College of Technology (Autonomous), "A" Grade by NAAC, UGC recognized 2(f) Status, Approved by AICTE – New Delhi, Affiliated to Anna University Namakkal – 03. www.selvamtech.edu.in

| 6. | Mention two assumptions made in slope deflection method. | |
|-----|---|-----|
| | i) Between each pair of the supports of the beam is constant. | CO2 |
| | ii) The joint in a structure may rotate or deflect as a whole, but the angles | |
| | between the members meeting at that joint remain the same. | |
| 7. | Mention any three reasons due to which sway may occur in portal frames. | CO2 |
| | Sway in portal frames may occur due to | |
| | i) Unsymmetry in geometry of the frame | |
| | ii) Unsymmetry in loading or | |
| | iii) Settlement of one end of a frame. | |
| | What are the quantities in terms of which the unknown moments are | CO2 |
| 8. | expressed in slope deflection method? | |
| 8. | In slope-deflection method, unknown moments are expressed in terms of | |
| | (i) Slopes (and) Deflections. | |
| 9. | What is the moment at a hinged end of a simple beam? | CO2 |
| | Moment at the hinged ends of a simple beam is zero. | |
| | The beam shown in figure is to be analyzed by slope deflection method. What | |
| 10. | are the unknowns and to determine them, what are the conditions used? | |
| | A B C | CO2 |
| | Unknowns are A,B,C | |
| | Equilibrium equations used: (i) MAB = 0 (ii) MBA + MBC = 0 (iii) MCB = 0 | |